

PLUG & DRAIN

Ready-to-use anti-flooding kit



- ※ **PLUG & DRAIN** is the essential emergency kit for fast and effective flood management in garages, basements, and cellars.
- ※ Features a high-performance drainage pump and a 12.5-metre-long PVC hose for quick water evacuation, plus the option to use the storage case as a filter.

- ※ **PLUG & DRAIN** efficiently lowers water to just about 2 mm from the ground, ensuring nearly complete removal.
- ※ Comes in a convenient carrying case that simplifies transport and doubles as a filter while you're draining.

PLUG & DRAIN Code. ASSKPDSTO2FA1

※ STANDARD COMPONENTS

SUBMERSIBLE Pump TOP2-FLOOR

- Single-phase **230 V - 50 Hz**
- Performance:
 - H max= **8.5 m**
 - Q max= **150 l/min**
- **10 metres** long power cable with Schuko plug
- Float switch
- **STORZ'** quick coupling
- Draining capability up to **2 mm** from the bottom



PVC HOSE

- **STORZ'** quick coupling
- Hose length **12.5 m**
- Pipe diameter **1 1/4"**



FILTER-BOX

- Features a secure pump attachment system for stable operation, with a quick-release option to use the pump independently
- Includes a cover for tidy storage, ensuring it's always ready for immediate use



※ PLUG & DRAIN WITH Pumps ON REQUEST

TOP3

- Performance:
- H max= **10.4 m**
 - Q max= **260 l/min**

CODE ASSKPDSTOP3A1



RXm 2

- Performance:
- H max= **10.3 m**
 - Q max= **190 l/min**

CODE ASSKPDSTRX2A1



RXm 3

- Performance:
- H max= **12.3 m**
 - Q max= **220 l/min**

CODE ASSKPDSTRX3A1





TECHNICAL SPECIFICATIONS		※ SERIES MODEL	※ AVAILABLE MODELS		
		TOP 2-FLOOR	TOP 3	RXm 2	RXm 3
SPECIFICATIONS	Pump type	Submersible	Submersible	Submersible	Submersible
	Pump control	Float	Float	Float	Float
MATERIALS	Pump body	Technopolymer	Technopolymer	AISI 304 stainless steel	AISI 304 stainless steel
	Impeller	Noryl™	Noryl™	AISI 304 stainless steel	AISI 304 stainless steel
	Mechanical seal	Ceramic/Graphite/NBR	Ceramic/Graphite/NBR	Ceramic/Graphite/NBR	Ceramic/Graphite/NBR
PERFORMANCE	Draining capability from the bottom	2 mm	14 mm	14 mm	14 mm
	Maximum depth of immersion	3 m	3 m	10 m	10 m
	Maximum size of suspended solids	2 mm	10 mm	10 mm	10 mm
FITTINGS	Pump connections	1 ¼" M	1 ¼" M	1 ¼" F	1 ¼" F
	Outlet port				
MOTOR ELECTRIC	Typology	Asynchronous (with automatic reset thermal protector)			
	Electric power supply	~ 230 V / 50 Hz			
	Consumption	450 W	700 W	450 W	800 W
	CURRENT AT FULL LOAD	2.0 A	3.2 A	2.0 A	3.6 A
	Power cord (pre-wired)	10 m with Schuko plug			
	Service index	Continuous running duty (S1)			

DIMENSIONS AND WEIGHT

TYPE	DIMENSIONS mm			kg*
	a	b	h	
PLUG & DRAIN - TOP 2-FLOOR	400	300	320	10.5
PLUG & DRAIN - TOP 3	400	300	362	12.9
PLUG & DRAIN - RXm 2	400	300	362	11.6
PLUG & DRAIN - RXm 3	400	300	362	13.1

(* Total weight: pump, hose, fittings and box)

